



The compact Krendl #475 **all-fiber** (airlock) unit is an economical machine for the **small professional contractor** or **do-it-yourself/rental** market. Designed for low maintenance and high production, the #475 provides a large easy loading hopper while offering simple rugged performance.

MATERIAL PRODUCTION RATE

*lbs/hr (kg/hr) rating with 150ft. (45.8m.) of 3" (7.6cm.) hose at 16ft. (4.8m.) elevation
Product density and variable blowing conditions will affect production rate.

| MATERIAL | MACHINE w/single 2-Stage Blower *lbs/hr (kg/hr) |
|-------------------|---|
| FIBERGLASS | 700 (317) |
| CELLULOSE | 2100 (952) |

SPECIFICATIONS

- **HOPPER CAPACITY** •
12.5 cu. ft. (.35 m³)
 - **WEIGHT** •
322 lbs. (146 kg.)
 - **DIMENSIONS** •
42 1/2"W x 29"D x 62"H
(108cm. W x 74cm. D x 157cm. H)
 - **AIRLOCK** •
12" x 10" diameter (30.5cm. x 25.4cm. diameter)
3" (7.6cm.) outlet for blowing hose
 - **POWER REQUIREMENT** •
double input, 15amps each/120volt/60hz
w/14amp blower
 - **BLOWERS/SIZES** •
Single 14amp/2-stage (120volt)
- **New Blower System**
Provides Airflow and Volume
of a Double Blower System.
140 CFM @ 3 1/2 PSI**

FEATURES

- **Low power requirements (Dual 15Amp 120V)**
- **Light weight machine**
- **Large 14 Amp/2-stage blower**
- **High output / easy maintenance airlock**
- **Material loading made easy with built in convertible tray**
- **Economical machine for the small contractor**



MECHANICAL AND ELECTRICAL FEATURES

Mechanical

- Modular component design for quick disassembly/reassembly for easy troubleshooting and maintenance.
- Safety guards provide operator protection.
- Removable hopper for quick and easy access to the airlock
- Dual (2) agitators that enhance the conditioning of fibers.
- All steel airlock for enhanced spraying and metering capabilities.
- 3/4 hp. TEFC motor for long life, Alum gearbox (745 in./lb. torque) for weight reduction.
- Extra heavy, nickel-plated #40 chain with hardened steel sprockets provides a corrosion/abrasion resistance drive system.
- Improved blower filter design for less filter maintenance.
- Cord hanger and hand pendant holder allow for convenient storage of cords and hand pendant.

Electrical

- Operator safety/Hazard features: emergency kill switch and manual override at machine.
- 150 ft. (46m.) remote control cord with three (3) position switch gives increased operator control of feed and blower.
- 15 amp thermal overload protection for complete protection of the agitator/material feed motor.
- 1 amp glass fuse protection for transformer providing properly sized fuse protection on the 2 amp transformer
- Multiple auxiliary convenience outlets for easy addition of accessory devices (i.e. wetting, wireless).

OPTIONAL ACCESSORIES

- Bushing reducer
- Internal Wetting System (IWS)
- Spray nozzles
- Wireless remote
- Hose
- Hose reel
- Wall scrubber

